

AN APPROXIMATE POWER PREDICTION METHOD

by

J. Holtrop* and G.G.J. Mennen*

1. Introduction

In a recent publication [1] a statistical method was presented for the determination of the required propulsive power at the initial design stage of a ship. This method was developed through a regression analysis of random model experiments and full-scale data, available at the Netherlands Ship Model Basin. Because the accuracy of the method was reported to be insufficient when unconventional combinations of main parameters were used, an attempt was made to extend the method by adjusting the original numerical prediction model to test data obtained in some specific cases. This adaptation of the method has resulted into a set of prediction formulae with a wider range of application. Nevertheless, it should be noticed that the given modifications have a tentative character only, because the adjustments are based on a small number of experiments. In any case, the application is limited to hull forms resembling the average ship described by the main dimensions and form coefficients used in the method.

The extension of the method was focussed on improving the power prediction of high-block ships with low L/B -ratios and of slender naval ships with a complex appendage arrangement and immersed transom sterns.

Some parts of this study were carried out in the scope of the NSMB Co-operative Research programme. The adaptation of the method to naval ships was carried out in a research study for the Royal Netherlands Navy. Permission to publish results of these studies is gratefully acknowledged.

2. Resistance prediction

The total resistance of a ship has been subdivided into:

$$R_{\text{total}} = R_F(1+k_1) + R_{APP} + R_W + R_B + R_{TR} + R_A$$

where:

- R_F frictional resistance according to the ITTC-1957 friction formula
- $1+k_1$ form factor describing the viscous resistance of the hull form in relation to R_F
- R_{APP} resistance of appendages
- R_W wave-making and wave-breaking resistance
- R_B additional pressure resistance of bulbous bow near the water surface

R_{TR} additional pressure resistance of immersed transom stern

R_A model-ship correlation resistance.

For the form factor of the hull the prediction formula:

$$1+k_1 = c_{13} \{0.93 + c_{12} (B/L_R)^{0.92497} (0.95 - C_P)^{-0.521448} (1 - C_P + 0.0225 lcb)^{0.6906}\}$$

can be used.

In this formula C_P is the prismatic coefficient based on the waterline length L and lcb is the longitudinal position of the centre of buoyancy forward of $0.5L$ as a percentage of L . In the form-factor formula L_R is a parameter reflecting the length of the run according to:

$$L_R/L = 1 - C_P + 0.06 C_P lcb / (4 C_P - 1)$$

The coefficient c_{12} is defined as:

$$c_{12} = (T/L)^{0.2228446} \quad \text{when } T/L > 0.05$$

$$c_{12} = 48.20(T/L - 0.02)^{2.078} + 0.479948 \quad \text{when } 0.02 < T/L < 0.05$$

$$c_{12} = 0.479948 \quad \text{when } T/L < 0.02$$

In this formula T is the average moulded draught. The coefficient c_{13} accounts for the specific shape of the afterbody and is related to the coefficient C_{stern} according to:

$$c_{13} = 1 + 0.003 C_{\text{stern}}$$

For the coefficient C_{stern} the following tentative guidelines are given:

Afterbody form	C_{stern}
V-shaped sections	- 10
Normal section shape	0
U-shaped sections with Hogner stern	+ 10

The wetted area of the hull can be approximated well by:

$$S = L(2T + B) \sqrt{C_M} (0.453 + 0.4425 C_B + 0.2862 C_M - 0.003467 B/T + 0.3696 C_{WP}) + 2.38 A_{BT}/C_B$$

In this formula C_M is the midship section coefficient, C_B is the block coefficient on the basis of the

* Netherlands Ship Model Basin, (Marin), Wageningen, The Netherlands.

waterline length L , C_{WP} is the waterplane area coefficient and A_{BT} is the transverse sectional area of the bulb at the position where the still-water surface intersects the stem.

The appendage resistance can be determined from:

$$R_{APP} = 0.5 \rho V^2 S_{APP} (1 + k_2)_{eq} C_F$$

where ρ is the water density, V the speed of the ship, S_{APP} the wetted area of the appendages, $1 + k_2$ the appendage resistance factor and C_F the coefficient of frictional resistance of the ship according to the ITTC-1957 formula.

In the Table below tentative $1 + k_2$ values are given for streamlined flow-oriented appendages. These values were obtained from resistance tests with bare and appended ship models. In several of these tests turbulence stimulators were present at the leading edges to induce turbulent flow over the appendages.

Approximate $1 + k_2$ values	
rudder behind skeg	1.5 – 2.0
rudder behind stern	1.3 – 1.5
twin-screw balance rudders	2.8
shaft brackets	3.0
skeg	1.5 – 2.0
strut bossings	3.0
hull bossings	2.0
shafts	2.0 – 4.0
stabilizer fins	2.8
dome	2.7
bilge keels	1.4

The equivalent $1 + k_2$ value for a combination of appendages is determined from:

$$(1 + k_2)_{eq} = \frac{\Sigma(1 + k_2)S_{APP}}{\Sigma S_{APP}}$$

The appendage resistance can be increased by the resistance of bow thruster tunnel openings according to:

$$\rho V^2 \pi d^2 C_{BTO}$$

where d is the tunnel diameter.

The coefficient C_{BTO} ranges from 0.003 to 0.012. For openings in the cylindrical part of a bulbous bow the lower figures should be used.

The wave resistance is determined from:

$$R_W = c_1 c_2 c_5 \nabla \rho g \exp \{ m_1 F_n^d + m_2 \cos(\lambda F_n^{-2}) \}$$

with:

$$c_1 = 2223105 c_7^{3.78613} (T/B)^{1.07961} (90 - i_E)^{-1.37565}$$

$$c_7 = 0.229577 (B/L)^{0.33333} \quad \text{when } B/L < 0.11$$

$$c_7 = B/L \quad \text{when } 0.11 < B/L < 0.25$$

$$c_7 = 0.5 - 0.0625 L/B \quad \text{when } B/L > 0.25$$

$$c_2 = \exp(-1.89 \sqrt{c_3})$$

$$c_5 = 1 - 0.8 A_T / (BT C_M)$$

In these expressions c_2 is a parameter which accounts for the reduction of the wave resistance due to the action of a bulbous bow. Similarly, c_5 expresses the influence of a transom stern on the wave resistance. In the expression A_T represents the immersed part of the transverse area of the transom at zero speed.

In this figure the transverse area of wedges placed at the transom chine should be included.

In the formula for the wave resistance, F_n is the Froude number based on the waterline length L . The other parameters can be determined from:

$$\lambda = 1.446 C_P - 0.03 L/B \quad \text{when } L/B < 12$$

$$\lambda = 1.446 C_P - 0.36 \quad \text{when } L/B > 12$$

$$m_1 = 0.0140407 L/T - 1.75254 \nabla^{1/3} / L + 4.79323 B/L - c_{16}$$

$$c_{16} = 8.07981 C_P - 13.8673 C_P^2 + 6.984388 C_P^3 \quad \text{when } C_P < 0.80$$

$$c_{16} = 1.73014 - 0.7067 C_P \quad \text{when } C_P > 0.80$$

$$m_2 = c_{15} C_P^2 \exp(-0.1 F_n^{-2})$$

The coefficient c_{15} is equal to -1.69385 for $L^3/\nabla < 512$, whereas $c_{15} = 0.0$ for $L^3/\nabla > 1727$.

For values of $512 < L^3/\nabla < 1727$, c_{15} is determined from:

$$c_{15} = -1.69385 + (L/\nabla^{1/3} - 8.0)/2.36$$

$$d = -0.9$$

The half angle of entrance i_E is the angle of the waterline at the bow in degrees with reference to the centre plane but neglecting the local shape at the stem. If i_E is unknown, use can be made of the following formula:

$$i_E = 1 + 89 \exp \{ - (L/B)^{0.80856} (1 - C_{WP})^{0.30484} (1 - C_P - 0.0225 lcb)^{0.6367} (L_R/B)^{0.34574} (100 \nabla/L^3)^{0.16302} \}$$

This formula, obtained by regression analysis of over 200 hull shapes, yields i_E values between 1° and 90° . The original equation in [1] sometimes resulted in negative i_E values for exceptional combinations of hull-form parameters.

The coefficient that determines the influence of the bulbous bow on the wave resistance is defined as:

$$c_3 = 0.56 A_{BT}^{1.5} / \{ BT(0.31 \sqrt{A_{BT}} + T_F - h_B) \}$$

where h_B is the position of the centre of the transverse area A_{BT} above the keel line and T_F is the forward draught of the ship.

The additional resistance due to the presence of a bulbous bow near the surface is determined from:

$$R_B = 0.11 \exp(-3 P_B^{-2}) F_{ni}^3 A_{BT}^{1.5} \rho g / (1 + F_{ni}^2)$$

where the coefficient P_B is a measure for the emergence of the bow and F_{ni} is the Froude number based on the immersion:

$$P_B = 0.56 \sqrt{A_{BT}} / (T_F - 1.5 h_B)$$

and

$$F_{ni} = V / \sqrt{g(T_F - h_B - 0.25 \sqrt{A_{BT}}) + 0.15 V^2}$$

In a similar way the additional pressure resistance due to the immersed transom can be determined:

$$R_{TR} = 0.5 \rho V^2 A_T c_6$$

The coefficient c_6 has been related to the Froude number based on the transom immersion:

$$c_6 = 0.2(1 - 0.2 F_{nT}) \quad \text{when } F_{nT} < 5$$

or

$$c_6 = 0 \quad \text{when } F_{nT} \geq 5$$

F_{nT} has been defined as:

$$F_{nT} = V / \sqrt{2 g A_T / (B + B C_{WP})}$$

In this definition C_{WP} is the waterplane area coefficient.

The model-ship correlation resistance R_A with

$$R_A = \frac{1}{2} \rho V^2 S C_A$$

is supposed to describe primarily the effect of the hull roughness and the still-air resistance. From an analysis of results of speed trials, which have been corrected to ideal trial conditions, the following formula for the correlation allowance coefficient C_A was found:

$$C_A = 0.006(L + 100)^{-0.16} - 0.00205 + 0.003 \sqrt{L/7.5} C_B^4 c_2 (0.04 - c_4)$$

with

$$c_4 = T_F / L \quad \text{when } T_F / L \leq 0.04$$

or

$$c_4 = 0.04 \quad \text{when } T_F / L > 0.04$$

In addition, C_A might be increased to calculate e.g. the effect of a larger hull roughness than standard. To this end the ITTC-1978 formulation can be used from which the increase of C_A can be derived for roughness values higher than the standard figure of $k_s = 150 \mu\text{m}$ (mean apparent amplitude):

$$\text{increase } C_A = (0.105 k_s^{1/3} - 0.005579) / L^{1/3}$$

In these formulae L and k_s are given in metres.

3. Prediction of propulsion factors

The statistical prediction formulae for estimating the effective wake fraction, the thrust deduction fraction and the relative-rotative efficiency as presented in [1] could be improved on several points.

For single-screw ships with a conventional stern arrangement the following adapted formula for the wake fraction can be used:

$$w = c_9 C_V \frac{L}{T_A} \left(0.0661875 + 1.21756 c_{11} \frac{C_V}{(1 - C_{P1})} \right) + 0.24558 \sqrt{\frac{B}{L(1 - C_{P1})}} \frac{0.09726}{0.95 - C_P} + \frac{0.11434}{0.95 - C_B} + 0.75 C_{\text{stern}} C_V + 0.002 C_{\text{stern}}$$

The coefficient c_9 depends on a coefficient c_8 defined as:

$$c_8 = BS / (LDT_A) \quad \text{when } B/T_A < 5$$

or

$$c_8 = S(7B/T_A - 25) / (LD(B/T_A - 3)) \quad \text{when } B/T_A > 5$$

$$c_9 = c_8 \quad \text{when } c_8 < 28$$

or

$$c_9 = 32 - 16 / (c_8 - 24) \quad \text{when } c_8 > 28$$

$$c_{11} = T_A / D \quad \text{when } T_A / D < 2$$

or

$$c_{11} = 0.0833333(T_A / D)^3 + 1.33333 \quad \text{when } T_A / D > 2$$

In the formula for the wake fraction, C_V is the viscous resistance coefficient with $C_V = (1 + k) C_F + C_A$. Further:

$$C_{P1} = 1.45 C_P - 0.315 - 0.0225 lcb.$$

In a similar manner the following approximate formula for the thrust deduction for single-screw ships with a conventional stern can be applied:

$$t = 0.001979 L / (B - BC_{P1}) + 1.0585 c_{10} + 0.00524 - 0.1418 D^2 / (BT) + 0.0015 C_{\text{stern}}$$

The coefficient c_{10} is defined as:

$$c_{10} = B/L \quad \text{when } L/B > 5.2$$

or

$$c_{10} = 0.25 - 0.003328402 / (B/L - 0.134615385) \quad \text{when } L/B < 5.2$$

The relative-rotative efficiency can be predicted

well by the original formula:

$$\eta_R = 0.9922 - 0.05908 A_E/A_O + \\ + 0.07424(C_P - 0.0225 lcb)$$

Because the formulae above apply to ships with a conventional stern an attempt has been made to indicate a tentative formulation for the propulsion factors of single-screw ships with an open stern as applied sometimes on slender, fast sailing ships:

$$w = 0.3 C_B + 10 C_V C_B - 0.1 \\ t = 0.10 \quad \text{and} \quad \eta_R = 0.98 .$$

These values are based on only a very limited number of model data. The influence of the fullness and the viscous resistance coefficient has been expressed in a similar way as in the original prediction formulae for twin-screw ships. These original formulae for twin-screw ships are:

$$w = 0.3095 C_B + 10 C_V C_B - 0.23 D/\sqrt{BT} \\ t = 0.325 C_B - 0.1885 D/\sqrt{BT} \\ \eta_R = 0.9737 + 0.111(C_P - 0.0225 lcb) + \\ - 0.06325 P/D$$

4. Estimation of propeller efficiency

For the prediction of the required propulsive power the efficiency of the propeller in open-water condition has to be determined. It has appeared that the characteristics of most propellers can be approximated well by using the results of tests with systematic propeller series. In [2] a polynomial representation is given of the thrust and torque coefficients of the B-series propellers. These polynomials are valid, however, for a Reynolds number of 2.10^6 and need to be corrected for the specific Reynolds number and the roughness of the actual propeller. The presented statistical prediction equations for the model-ship correlation allowance and the propulsion factors are based on Reynolds and roughness corrections according to the ITTC-1978 method, [3]. According to this method the propeller thrust and torque coefficients are corrected according to:

$$K_{T\text{-ship}} = K_{T\text{-B-series}} + \Delta C_D 0.3 \frac{P c_{0.75} Z}{D^2} \\ K_{Q\text{-ship}} = K_{Q\text{-B-series}} - \Delta C_D 0.25 \frac{c_{0.75} Z}{D}$$

Here ΔC_D is the difference in drag coefficient of the profile section, P is the pitch of the propeller and

$c_{0.75}$ is the chord length at a radius of 75 per cent and Z is the number of blades.

$$\Delta C_D = (2 + 4(t/c)_{0.75}) \{0.003605 - (1.89 + 1.62 \\ \log(c_{0.75}/k_p))^{-2.5}\}$$

In this formula t/c is the thickness–chordlength ratio and k_p is the propeller blade surface roughness.

For this roughness the value of $k_p = 0.00003$ m is used as a standard figure for new propellers.

The chord length and the thickness-chordlength ratio can be estimated using the following empirical formulae:

$$c_{0.75} = 2.073(A_E/A_O) D/Z$$

and

$$(t/c)_{0.75} = (0.0185 - 0.00125 Z) D/c_{0.75} .$$

The blade area ratio can be determined from e.g. Keller's formula:

$$A_E/A_O = K + (1.3 + 0.3 Z) T/(D^2(p_o + \rho gh - p_v))$$

In this formula T is the propeller thrust, $p_o + \rho gh$ is the static pressure at the shaft centre line, p_v is the vapour pressure and K is a constant to which the following figures apply:

$$K = 0 \text{ to } 0.1 \text{ for twin-screw ships}$$

$$K = 0.2 \text{ for single-screw ships}$$

For sea water of 15 degrees centigrade the value of $p_o - p_v$ is 99047 N/m^2 .

The given prediction equations are consistent with a shafting efficiency of

$$\eta_S = P_D/P_S = 0.99$$

and reflect ideal trial conditions, implying:

- no wind, waves and swell,
- deep water with a density of 1025 kg/m^3 and a temperature of 15 degrees centigrade and
- a clean hull and propeller with a surface roughness according to modern standards.

The shaft power can now be determined from:

$$P_S = P_E/(\eta_R \eta_o \eta_S \frac{1-t}{1-w})$$

5. Numerical example

The performance characteristics of a hypothetical single-screw ship are calculated for a speed of 25 knots. The calculations are made for the various resistance components and the propulsion factors, successively.

The main ship particulars are listed in the Table on the next page:

Main ship characteristics

length on waterline	L	205.00 m
length between perpendiculars	L_{pp}	200.00 m
breadth moulded	B	32.00 m
draught moulded on F.P.	T_F	10.00 m
draught moulded on A.P.	T_A	10.00 m
displacement volume moulded	∇	37500 m ³
longitudinal centre of buoyancy		2.02% aft of $\frac{1}{2}L_{pp}$
transverse bulb area	A_{BT}	20.0 m ²
centre of bulb area above keel line	h_B	4.0 m
midship section coefficient	C_M	0.980
waterplane area coefficient	C_{WP}	0.750
transom area	A_T	16.0 m ²
wetted area appendages	S_{APP}	50.0 m ²
stern shape parameter	C_{stern}	10.0
propeller diameter	D	8.00 m
number of propeller blades	Z	4
clearance propeller with keel line		0.20 m
ship speed	V	25.0 knots

References

- Holtrop, J. and Mennen, G.G.J., 'A statistical power prediction method', International Shipbuilding Progress, Vol. 25, October 1978.
- Oosterveld, M.W.C. and Oossanen, P. van, 'Further computer analyzed data of the Wageningen B-screw series', International Shipbuilding Progress, July 1975.
- Proceedings 15th ITTC, The Hague, 1978.

The calculations with the statistical method resulted into the following coefficients and powering characteristics listed in the next Table:

F_n	= 0.2868	F_{nT}	= 5.433
C_P	= 0.5833	R_{TR}	= 0.00 kN
L_R	= 81.385 m	c_4	= 0.04
lcb	= -0.75% (relative to $\frac{1}{2}L$)	C_A	= 0.000352
c_{12}	= 0.5102	R_A	= 221.98 kN
c_{13}	= 1.030	R_{total}	= 1793.26 kN
$1 + k_1$	= 1.156	P_E	= 23063 kW
S	= 7381.45 m ²	C_V	= 0.001963
C_F	= 0.001390	c_9	= 14.500
R_F	= 869.63 kN	c_{11}	= 1.250
$1 + k_2$	= 1.50	C_{P1}	= 0.5477
R_{APP}	= 8.83 kN	w	= 0.2584
c_7	= 0.1561	c_{10}	= 0.15610
i_E	= 12.08 degrees	t	= 0.1747
c_1	= 1.398	T	= 2172.75 kN
c_3	= 0.02119	A_E/A_O	= 0.7393
c_2	= 0.7595	η_R	= 0.9931
c_5	= 0.9592	$c_{0.75}$	= 3.065 m
m_1	= -2.1274	$t/c_{0.75}$	= 0.03524
c_{15}	= 1.69385	ΔC_D	= 0.000956
m_2	= -0.17087		
λ	= 0.6513	From the B-series polynomials:	
R_W	= 557.11 kN	K_{Ts}	= 0.18802
P_B	= 0.6261	n	= 1.6594 Hz
F_{ni}	= 1.5084	K_{Qo}	= 0.033275
R_B	= 0.049 kN	η_o	= 0.6461
		P_S	= 32621 kW